

## Description

FS Clean Flow's patented technology was designed to meet the challenges of direct injection technology by preventing formation and laydown of gum and dispersing coke that may have formed. FS Clean Flow enhances fuel with additional detergents to keep engines clean, which improves performance and reliability while protecting against deposit buildup and corrosion.

## Features and Benefits

- Helps to keep clean and clean-up intake valves and injectors, which can result in:
  - Optimized fuel economy
  - Maximized power and acceleration
  - Reduced emissions
- Patented for use in DIG engines (U.S. Patent 7,491,248)
- Up to E20 ethanol compatible
- Excellent combustion chamber deposit control
- Good demulsibility
- A-rating corrosion protection
- Low viscosity for easy handling
- Engine benefits include:
  - Significant reduction in deposits
  - Reduced emissions
  - Reduced hesitation and drivability upsets
  - Improved fuel economy
  - Starting clean, cleaning up, and staying clean

## Typical Properties

Physical State	Liquid
Color	Amber Liquid
Density, lbs. /gal.	7.58
Specific Gravity @ 15.6/15.6 °C	0.9099
Flash Point, °C (PMCC)	50°C (122°F)
Pour Point, °C	-50 max.
Viscosity @ 40°C, cSt	12
Viscosity @ -20°C, cSt	400 max.

## Recommended Usage

1 oz. treats 50 gallons  
10 oz. treats 500 gallons  
1 gallon treats 6667 gallons

## Storage and Handling

Max handling temp. 35°C (up to 80°C under nitrogen)

## Shelf Life

24 months